

Latex DL 822NA for Carpet Backing

Carboxylated Styrene Butadiene Latex

Typical Latex Properties¹

Property	Value
Solids	51%
pH	7.5
Glass transition temperature (Tg) ²	- 15 °C
Brookfield viscosity	<500 cPs (#2 @50rpm)
Minimum film formation temperature (MFFT)	<32 °F

¹ Notes: Not to be construed as specifications, ² Measured by DSC

Applications

Latex DL 822NA is specifically designed for Artificial Grass, Residential carpet, Automotive carpet, Commercial carpet, and Woven carpet applications requiring very soft hand and excellent wet strength. This product can be used for both precoat and secondary coating applications. Latex DL 822NA demonstrates “legs” like natural rubber.

Benefits

- Very soft hand
- High wet strength
- Similar to natural rubber

Food Contact Compliance Status

- Non-food contact

Styron is a world leader in the manufacture of emulsion polymers used in the production of carpet and other floor covering materials. Our products include a wide variety of styrene butadiene, ignition resistant, and acrylic latexes to meet specific needs for the carpet industry. Latex is used to impart specific physical properties to the finished carpet, including dimensional stability, stiffness and hand, and may be used to enhance performance properties of the carpet, including ignition resistance and moisture barrier.

NOTE: The use(s) cited above are subject to good manufacturing practices and any limitations, which are part of the regulations. The regulations should be consulted for complete details. It is the responsibility of the package manufacturer and/or food packager to ensure that the final food-contact article is suitable for its intended use.

Contact Information:

North America
 U.S. and Canada: 1-888-STYRON
 1-989-633-1718
 Mexico: +1-800-441-4369

www.styron.com

NOTICE: Any products with the prefix "XU", "XZ", "XQ" or "XG" are experimental and may not become available for commercial sale. No freedom from any patent owned by Styron or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, recipient is responsible for determining whether products and the information in this document are appropriate for recipient's use and for ensuring that recipient's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Styron assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.